

MSDS Browser Format

MSDS Pdf Download

Petroleum Ether
Material Safety Data Sheet

Navigation Key

[1. Chemical Product and Company Identification](#)

[2. Composition / Information on Ingredients](#)

[3. Hazards Identification](#)

[4. First Aid Measures](#)

[5. Fire Fighting Measure](#)

[6. Accidental Release Measure](#)

[7. Handling and Storage](#)

[8. Exposure Controls / Personal Protection](#)

[9. Physical and Chemical Properties](#)

[10. Stability and Reactivity](#)

[11. Toxicological Information](#)

[12. Ecological Information](#)

[13. Disposal Considerations](#)

[14. Transport Information](#)

[15. Regulatory Information](#)

[16. Other Information](#)

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

[BACK TO KEY](#)

PRODUCT NAME: Petroleum Ether

OTHER/GENERIC NAMES: Ligroin, Petroleum Spirits, Petroleum distillates, VM&P Naptha.

PRODUCT USE: Solvent

MANUFACTURER: Honeywell

FOR MORE INFORMATION**CALL:**

(Monday-Friday, 9:00am-4:30pm)
 Product Safety Department
 800.368.0050
 231.726.3171

IN CASE OF EMERGENCY**CALL:**

(24 Hours/Day, 7 Days/Week)
 973-455-2000 (Honeywell,
 Morristown, NJ)
 1-800-424-9300 (Chemtrec)

2. COMPOSITION/INFORMATION ON INGREDIENTS[BACK TO KEY](#)

INGREDIENT NAME	CAS NUMBER	WEIGHT %
Petroleum Ether	8032-32-4	~100

Trace impurities and additional material names not listed above may also appear in Section 15 toward the end of the MSDS. These materials may be listed for local "Right-To-Know" compliance and for other reasons.

3. HAZARDS IDENTIFICATION[BACK TO KEY](#)**EMERGENCY OVERVIEW:**

Extremely Flammable. Clear volatile liquid. Moderately toxic by ingestion. Mildly toxic by inhalation.


POTENTIAL HEALTH HAZARDS

SKIN: Irritant. Can cause dermatitis through defatting of the skin.

EYES: Irritant. Liquid and vapor concentration can cause redness and itching.

INHALATION: Can cause headache, nausea, drowsiness, vomiting, disorientation, and loss of consciousness. Can cause lung and kidney damage. A central nervous system depressant

INGESTION: Do not induce vomiting unless instructed to do so by a physician. Get medical assistance immediately.



DELAYED EFFECTS: Can cause damage to the respiratory tract, kidneys, and central nervous system.

FLAME PROPAGATION RATE (solids):
OSHA FLAMMABILITY CLASS:

Not Applicable
IA

EXTINGUISHING MEDIA:

Carbon dioxide, dry chemical or alcohol foam.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Dangerous fire hazard when exposed to heat or flame. Vapor is heavier than air and danger of flashback exists.

SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS:

Do not release runoff from fire fighting efforts to sewers or waterways. Fire may produce toxic fumes. Always wear Self Contained Breathing Apparatus.

[6. ACCIDENTAL RELEASE MEASURES](#)

[BACK TO KEY](#)

IN CASE OF SPILL OR OTHER RELEASE:

(Always wear recommended personal protective equipment.) Eliminate sources of ignition. Isolate the spill area. Stop leak in a safe and practical manner. (If leak cannot be stopped easily and safely, advise trained emergency response personnel of the situation.) Using inert material (such as ground corncobs) dike the spilled solvent to prevent it from running into drains or waterways.

Spills and releases may have to be reported to Federal and/or local authorities. See Section 15 regarding reporting requirements.

[7. HANDLING AND STORAGE](#)

[BACK TO KEY](#)

NORMAL HANDLING:

(Always wear recommended personal protective equipment.) Flammable liquid and vapors. Keep container closed. Do not breathe vapors. Avoid contact with skin, eyes and mucous membranes. Keep away from heat, sparks and flame. Electrically ground all handling equipment. Protective neoprene or rubber gloves and apron are recommended. Ensure contents are at or below room temperature before opening container(s).

STORAGE RECOMMENDATIONS:

Store in an area designed for storage of flammable liquids. (OSHA 29 CFR 1910.106)

Protect from temperature extremes and sunlight, and store away from incompatible substances and in accordance with 29 CFR 1910.106. Avoid acids, bases, oxidizers, explosives, nitrogen-fluorine compounds, sulfites, perchlorates. Flammable liquid and vapor. Once liquid solvent has been completely dispensed, containers which appear "empty" should be handled in the same manner as when they were "full" of liquid solvent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

[BACK TO KEY](#)

ENGINEERING CONTROLS:

Provide general or local exhaust ventilation systems to maintain airborne concentrations below exposure limits. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

PERSONAL PROTECTIVE EQUIPMENT

SKIN PROTECTION:

Wear chemically protective gloves, boots and aprons to prevent prolonged or repeated skin contact.

EYE PROTECTION:

Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices.

RESPIRATORY PROTECTION:

Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

ADDITIONAL RECOMMENDATIONS:

Ensure that emergency eyewash stations and washing facilities are available in work area..

EXPOSURE GUIDELINES

INGREDIENT NAME	ACGIH TLV	OSHA PEL	OTHER LIMIT
Petroleum Ether	300 ppm	300 ppm	None

* = Limit established by Honeywell.

** = Workplace Environmental Exposure Level (AIHA).

*** = Biological Exposure Index (ACGIH).

OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

[BACK TO KEY](#)

APPEARANCE:	Clear, colorless
PHYSICAL STATE:	Liquid
MOLECULAR WEIGHT:	Not determined
CHEMICAL FORMULA:	Mixture of paraffins, naphthas, and other hydrocarbons.
ODOR:	Gasoline like odor
SPECIFIC GRAVITY (water = 1.0):	0.64 g/ml @ 20°C
SOLUBILITY IN WATER (weight %):	0.04% @ 20°C
pH:	Not Applicable
BOILING POINT:	(35°C - 60°C):
MELTING POINT:	<-73°C
VAPOR PRESSURE:	40 mm Hg @ 20°C
VAPOR DENSITY (air = 1.0):	3
EVAPORATION RATE:	>10 COMPARED TO: Butyl Acetate = 1
% VOLATILES:	100%
FLASH POINT:	55°F (13°C)

(Flash point method and additional flammability data are found in Section 5.)

10. STABILITY AND REACTIVITY

usual and reasonable storage and handling conditions.

INCOMPATIBILITIES:

Strong Oxidizers.

CONDITIONS TO AVOID:

Oxidizers, Strong Acids, Heat and other ignition sources.

HAZARDfn-2.2603 TD (CONDITIONS S7u22TOS6 1 T PRODUCT

Yes

If yes, the RCRA ID number is: D001

OTHER DISPOSAL CONSIDERATIONS:

Dispose of material in accordance with all applicable local, state, and federal regulations. The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

[14. TRANSPORT INFORMATION](#)

[BACK TO KEY](#)

US DOT PROPER SHIPPING NAME:	Petroleum distillates n.o.s.
US DOT HAZARD CLASS:	3, Flammable Liquid
US DOT ID NUMBER:	UN1268
US DOT PACKING GROUP:	I
NA EMERGENCY RESPONSE GUIDE:	128

BACK15.Tj 36oID number is: D001

Spills or releases resulting in the loss of any ingredient at or above its RQ requires immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

SECTION 311 HAZARD CLASS: Acute, Fire, Reactive

SARA 313 TOXIC CHEMICALS:

The following ingredients are SARA 313 "Toxic Chemicals". CAS numbers and weight percents are found in Section 2.

INGREDIENT NAME	Comment)
No ingredients listed in this section.	

STATE RIGHT-TO-KNOW

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

INGREDIENT NAME	WEIGHT %	Comment)
No ingredients listed in this section.		

Health: 1
Flammability: 4
Reactivity: 0

Copyright © 2000 Honeywell.
All rights reserved
Please send any comments to
webmaster@honeywell.com

Y2K Readiness Disclosure